

<b>REPORT DOCUMENTATION PAGE</b>			Form Approved OMB NO. 0704-0188		
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA, 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>					
1. REPORT DATE (DD-MM-YYYY)		2. REPORT TYPE New Reprint		3. DATES COVERED (From - To) -	
4. TITLE AND SUBTITLE Joint Sparse Representation for Robust Multimodal Biometrics Recognition			5a. CONTRACT NUMBER W911NF-09-1-0383		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER 611103		
6. AUTHORS Vishal M. Patel, Nasser M. Nasrabadi, Rama Chellappa, Sumit Shekhar			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAMES AND ADDRESSES William Marsh Rice University 6100 Main St., MS-16  Houston, TX 77005 -1827				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS (ES) U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211				10. SPONSOR/MONITOR'S ACRONYM(S) ARO	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) 56177-CS-MUR.215	
12. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.					
14. ABSTRACT Traditional biometric recognition systems rely on a single biometric signature for authentication. While the advantage of using multiple sources of information for establishing the identity has been widely recognized, computational models for multimodal biometrics recognition have only recently received attention. <del>We propose a multimodal sparse representation method,</del>					
15. SUBJECT TERMS Multimodal biometrics, feature fusion, sparse representation					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	15. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON Richard Baraniuk
a. REPORT UU	b. ABSTRACT UU	c. THIS PAGE UU			19b. TELEPHONE NUMBER 713-348-5132

## Report Title

Joint Sparse Representation for Robust Multimodal Biometrics Recognition

### ABSTRACT

Traditional biometric recognition systems rely on a single biometric signature for authentication. While the advantage of using multiple sources of information for establishing the identity has been widely recognized, computational models for multimodal biometrics recognition have only recently received attention. We propose a multimodal sparse representation method, which represents the test data by a sparse linear combination of training data, while constraining the observations from different modalities of the test subject to share their sparse representations. Thus, we simultaneously take into account correlations as well as coupling information among biometric modalities. We modify our model so that it is robust to noise and occlusion. A multimodal quality measure is also proposed to weigh each modality as it gets fused. Furthermore, we also kernelize the algorithm to handle non-linearity in data. The optimization problem is solved using an efficient alternative direction method. Various experiments show that our method compares favorably with competing fusion-based methods.

---

## REPORT DOCUMENTATION PAGE (SF298) (Continuation Sheet)

---

Continuation for Block 13

ARO Report Number 56177.215-CS-MUR  
Joint Sparse Representation for Robust Multimc...

Block 13: Supplementary Note

© 2014 . Published in IEEE Transactions on Pattern Analysis and Machine Intelligence, Vol. Ed. 0 36, (1) (2014), (, (1). DoD Components reserve a royalty-free, nonexclusive and irrevocable right to reproduce, publish, or otherwise use the work for Federal purposes, and to authroize others to do so (DODGARS §32.36). The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.

Approved for public release; distribution is unlimited.

# Joint Sparse Representation for Robust Multimodal Biometrics Recognition

Sumit Shekhar, *Student Member, IEEE*, Vishal M. Patel, *Member, IEEE*, Nasser M. Nasrabadi, *Fellow, IEEE*,  
and Rama Chellappa, *Fellow, IEEE*

**Abstract**—Traditional biometric recognition systems rely on a single biometric signature for authentication. While the advantage of using multiple sources of information for establishing the identity has been widely recognized, computational models for multimodal biometrics recognition have only recently received attention. We propose a multimodal sparse representation method, which represents the test data by a sparse linear combination of training data, while constraining the observations from different modalities of the test subject to share their sparse representations. Thus, we simultaneously take into account correlations as well as coupling information among biometric modalities. We modify our model so that it is robust to noise and occlusion. A multimodal quality measure is also proposed to weigh each modality as it gets fused. Furthermore, we also kernelize the algorithm to handle non-linearity in data. The optimization problem is solved using an efficient alternative direction method. Various experiments show that our method compares favorably with competing fusion-based methods.

**Index Terms**—Multimodal biometrics, feature fusion, sparse representation.

## I. INTRODUCTION

Unimodal biometric systems rely on a single source of information such as a single iris or fingerprint or face for authentication [1]. Unfortunately these systems have to deal with some of the following inevitable problems [2]: (a) Noisy data: poor lighting on a user's face or occlusion are examples of noisy data. (b) Non-universality: the biometric system based on a single source of evidence may not be able to capture meaningful data from some users. For instance, an iris biometric system may extract incorrect texture patterns from the iris of certain users due to the presence of contact lenses. (c) Intra-class variations: in the case of fingerprint recognition, presence of wrinkles due to wetness [3] can cause these variations. These types of variations often occur when a user incorrectly interacts with the sensor. (d) Spoof attack: hand signature forgery is an example of this type of attack. It has been observed that some of the limitations of unimodal biometric systems can be addressed by deploying multimodal biometric systems that essentially integrate the evidence presented by multiple sources of information such as iris, fingerprints and face. Such systems are less vulnerable to spoof attacks as it would be difficult for an imposter to

simultaneously spoof multiple biometric traits of a genuine user. Due to sufficient population coverage, these systems are able to address the problem of non-universality.

Classification in multibiometric systems is done by fusing information from different biometric modalities. The information fusion can be done at different levels, which can be broadly divided into feature level, score level and rank/decision level fusion. Due to preservation of raw information, feature level fusion can be more discriminative than score or decision level fusion [4]. But, there have been very few efforts in exploring feature level fusion in the biometric community. This is because of the differences in features extracted from different sensors in terms of type and dimensions. Often the features have large dimensions, and fusion becomes difficult at the feature level. The prevalent method is feature concatenation, which has been used for different multibiometric settings [5]–[7]. However, for high-dimensional feature vectors, simple feature concatenation may be inefficient and non-robust. A related work in the machine learning literature is of Multiple Kernel Learning (MKL), which aims to integrate information from different features by learning a weighted combination of respective kernels. A detailed survey of the methods for MKL can be found in [8]. However, for multimodal systems, weight determination during testing is important, based on the quality of different modalities. Such a framework is not feasible in MKL setting. Methods like [9], [10] try to exploit information from labeled and unlabeled data from a different view to improve classifier performance. Similarly, SVM-2k [11] jointly learns SVM for two views. But, these methods are difficult to generalize to multimodal setting, as common in biometric fusion. A Fisher discriminant analysis based method has also been proposed for integrating multiple views [12], but it is also similar to MKL with kernel Fisher discriminant analysis as the base learner [13].

In recent years, theories of Sparse Representation (SR) and Compressed Sensing (CS) have emerged as powerful tools for efficient processing of data in non-traditional ways [14]. This has led to a resurgence in interest in the principles of SR and CS for biometrics recognition [15]. Wright *et al.* [16] proposed the seminal sparse representation-based classification (SRC) algorithm for face recognition. It was shown that by exploiting the inherent sparsity of data, one can obtain improved recognition performance over traditional methods especially when the data is contaminated by various artifacts such as illumination variations, disguise, occlusion

Sumit Shekhar, Vishal M. Patel and R. Chellappa are with the Department of Electrical and Computer Engineering and the Center for Automation Research, UMIACS, University of Maryland, College Park, MD 20742 USA (e-mail: {sshekha,pvishalm,rama}@umiacs.umd.edu)

Nasser M. Nasrabadi is with the U.S. Army Research Lab, Adelphi, MD 20783 USA (e-mail: nasser.m.nasrabadi@us.army.mil).




Fig. 1: Overview of our algorithm.

and random pixel corruption. Pillai *et al.* extended this work for robust cancelable iris recognition in [17]. Nagesh and Li [18] presented an expression-invariant face recognition method using distributed CS and joint sparsity models. Patel *et al.* [19] proposed a dictionary-based method for face recognition under varying pose and illumination. A discriminative dictionary learning method for face recognition was also proposed by Zhang and Li [20]. For a survey of applications of SR and CS algorithms to biometric recognition, see [14], [15], [21], [22] and the references therein.

Motivated by the success of SR in unimodal biometric recognition, we propose a joint sparsity-based algorithm for multimodal biometrics recognition. Figure 1 presents an overview of our framework. It is based on the well known regularized regression method, multi-task multi-variate Lasso [23], [24]. Our method imposes common sparsities both within each biometric modality and across different modalities. Note that our method is different from some of the previously proposed classification algorithms based on joint sparse representation. For example, Yuan and Yan [25] proposed a multi-task sparse linear regression model for image classification. This method uses group sparsity to combine different features of an object for classification. Zhang *et al.* [26] proposed a joint dynamic sparse representation model for object recognition. Their essential goal was to recognize the same object viewed from multiple observations i.e., different poses. Our method is more general in that it can deal with both multi-modal as well as multi-variate sparse representations.

This paper makes the following contributions:

- We present a robust feature level fusion algorithm for multibiometric recognition. Through the proposed joint sparse framework, we can easily handle different dimen-

sions of different modalities by forcing different features to interact through their sparse coefficients. Furthermore, the proposed algorithm can efficiently handle large dimensional feature vectors.

- We make the classification robust to occlusion and noise by introducing an error term into the optimization framework.
- The algorithm is easily generalizable to handle multiple test inputs from a modality.
- We introduce a quality measure for multimodal fusion based on the joint sparse representation.
- Lastly, we kernelize the algorithm to handle non-linearity in the data samples.

A preliminary version of this work appeared in [27], which describes just the linear version of the algorithm, robust to noise and occlusion. Furthermore, extensive experimental evaluations are presented here.

#### A. Paper Organization

The paper is organized as follows. In section II, we describe the proposed sparsity-based multimodal recognition algorithm which is kernelized in section IV. The quality measure is described in III. Experimental evaluations on a comprehensive multimodal dataset and a face database are described in section V. Finally, in section VI, we discuss the computational complexity of the method. Concluding remarks are presented in section VII.

## II. JOINT SPARSITY-BASED MULTIMODAL BIOMETRICS RECOGNITION

Consider a multimodal  $C$ -class classification problem with  $D$  different biometric traits. Suppose there are  $p_i$  training

samples in each biometric trait. For each biometric trait  $i = 1, \dots, D$ , we denote

$$\mathbf{X}^i = [\mathbf{X}_1^i, \mathbf{X}_2^i, \dots, \mathbf{X}_C^i]$$

as an  $n_i \times p_i$  dictionary of training samples consisting of  $C$  sub-dictionaries  $\mathbf{X}_k^i$ 's corresponding to  $C$  different classes. Each sub-dictionary

$$\mathbf{X}_j^i = [\mathbf{x}_{j,1}^i, \mathbf{x}_{j,2}^i, \dots, \mathbf{x}_{j,p_j}^i] \in \mathbb{R}^{n_i \times p_j}$$

represents a set of training data from the  $i$ th modality labeled with the  $j$ th class. Note that  $n_i$  is the feature dimension of each sample and there are  $p_j$  number of training samples in class  $j$ . Hence, there are a total of  $p = \sum_{j=1}^C p_j$  many samples in the dictionary  $\mathbf{X}_C^i$ . Elements of the dictionary are often referred to as atoms. In multimodal biometrics recognition problem, given a test samples (matrix)  $\mathbf{Y}$ , which consists of  $D$  different modalities  $\{\mathbf{Y}^1, \mathbf{Y}^2, \dots, \mathbf{Y}^D\}$  where each sample  $\mathbf{Y}^i$  consists of  $d_i$  observations  $\mathbf{Y}^i = [\mathbf{y}_1^i, \mathbf{y}_2^i, \dots, \mathbf{y}_{d_i}^i] \in \mathbb{R}^{n_i \times d_i}$ , the objective is to identify the class to which a test sample  $\mathbf{Y}$  belongs to. In what follows, we present a multimodal multivariate sparse representation-based algorithm for this problem [23], [24], [28].

#### A. Multimodal multivariate sparse representation

We want to exploit the joint sparsity of coefficients from different biometric modalities to make a joint decision. To simplify this model, let us consider a bi-modal classification problem where the test sample  $\mathbf{Y} = [\mathbf{Y}^1, \mathbf{Y}^2]$  consists of two different modalities such as iris and face. Suppose that  $\mathbf{Y}^1$  belongs to the  $j$ th class. Then, it can be reconstructed by a linear combination of the atoms in the sub-dictionary  $\mathbf{X}_j^1$ . That is,  $\mathbf{Y}^1 = \mathbf{X}^1 \mathbf{\Gamma}^1 + \mathbf{N}^1$ , where  $\mathbf{\Gamma}^1$  is a sparse matrix with only  $p_j$  nonzero rows associated with the  $j$ th class and  $\mathbf{N}^1$  is the noise matrix. Similarly, since  $\mathbf{Y}^2$  represents the same subject, it belongs to the same class and can be represented by training samples in  $\mathbf{X}_j^2$  with different set of coefficients  $\mathbf{\Gamma}_j^2$ . Thus, we can write  $\mathbf{Y}^2 = \mathbf{X}^2 \mathbf{\Gamma}^2 + \mathbf{N}^2$ , where  $\mathbf{\Gamma}^2$  is a sparse matrix that has the same sparsity pattern as  $\mathbf{\Gamma}^1$ . If we let  $\mathbf{\Gamma} = [\mathbf{\Gamma}^1, \mathbf{\Gamma}^2]$ , then  $\mathbf{\Gamma}$  is a sparse matrix with only  $p_j$  non-zero rows.

In the more general case where we have  $D$  modalities, if we denote  $\{\mathbf{Y}^i\}_{i=1}^D$  as a set of  $D$  observations each consisting of  $d_i$  samples from each modality and let  $\mathbf{\Gamma} = [\mathbf{\Gamma}^1, \mathbf{\Gamma}^2, \dots, \mathbf{\Gamma}^D] \in \mathbb{R}^{p \times d}$  be the matrix formed by concatenating the coefficient matrices with  $d = \sum_{i=1}^D d_i$ , then we can seek for the row-sparse matrix  $\mathbf{\Gamma}$  by solving the following  $\ell_1/\ell_q$ -regularized least square problem

$$\hat{\mathbf{\Gamma}} = \arg \min_{\mathbf{\Gamma}} \frac{1}{2} \sum_{i=1}^D \|\mathbf{Y}^i - \mathbf{X}^i \mathbf{\Gamma}^i\|_F^2 + \lambda \|\mathbf{\Gamma}\|_{1,q} \quad (1)$$

where  $\lambda$  is a positive parameter and  $q$  is set greater than 1 to make the optimization problem convex. Here,  $\|\mathbf{\Gamma}\|_{1,q}$  is a norm defined as  $\|\mathbf{\Gamma}\|_{1,q} = \sum_{k=1}^p \|\gamma^k\|_q$  where  $\gamma^k$ 's are the row vectors of  $\mathbf{\Gamma}$  and  $\|\mathbf{Y}\|_F$  is the Frobenius norm of the matrix  $\mathbf{Y}$  defined as  $\|\mathbf{Y}\|_F = \sqrt{\sum_{i,j} Y_{i,j}^2}$ . Once  $\hat{\mathbf{\Gamma}}$  is obtained, the

class label associated with an observed vector is then declared as the one that produces the smallest approximation error.

$$\hat{j} = \arg \min_j \sum_{i=1}^D \|\mathbf{Y}^i - \mathbf{X}^i \delta_j^i(\mathbf{\Gamma}^i)\|_F^2, \quad (2)$$

where  $\delta_j^i$  is the matrix indicator function defined by keeping rows corresponding to the  $j$ th class and setting all other rows equal to zero. Note that the optimization problem (1) reduces to the conventional Lasso [29] when  $D = 1$  and  $d = 1$ . In the case, when  $D = 1$  (1) is referred to as multivariate Lasso [23].

#### B. Robust multimodal multivariate sparse representation

In this section, we consider a more general problem where the data is contaminated by noise. In this case, the observation model can be modeled as

$$\mathbf{Y}^i = \mathbf{X}^i \mathbf{\Gamma}^i + \mathbf{Z}^i + \mathbf{N}^i, \quad i = 1, \dots, D, \quad (3)$$

where  $\mathbf{N}^i$  is a small dense additive noise and  $\mathbf{Z}^i \in \mathbb{R}^{n_i \times d_i}$  is a matrix of background noise (occlusion) with arbitrarily large magnitude. One can assume that each  $\mathbf{Z}^i$  is sparsely represented in some basis  $\mathbf{B}^i \in \mathbb{R}^{n_i \times m_i}$ . That is,  $\mathbf{Z}^i = \mathbf{B}^i \mathbf{\Lambda}^i$  for some sparse matrices  $\mathbf{\Lambda}^i \in \mathbb{R}^{m_i \times d_i}$ . Hence, (3) can be rewritten as

$$\mathbf{Y}^i = \mathbf{X}^i \mathbf{\Gamma}^i + \mathbf{B}^i \mathbf{\Lambda}^i + \mathbf{N}^i, \quad i = 1, \dots, D, \quad (4)$$

With this model, one can simultaneously recover the coefficients  $\mathbf{\Gamma}^i$  and  $\mathbf{\Lambda}^i$  by taking advantage of the fact that  $\mathbf{\Lambda}^i$  are sparse

$$\hat{\mathbf{\Gamma}}, \hat{\mathbf{\Lambda}} = \arg \min_{\mathbf{\Gamma}, \mathbf{\Lambda}} \frac{1}{2} \sum_{i=1}^D \|\mathbf{Y}^i - \mathbf{X}^i \mathbf{\Gamma}^i - \mathbf{B}^i \mathbf{\Lambda}^i\|_F^2 + \lambda_1 \|\mathbf{\Gamma}\|_{1,q} + \lambda_2 \|\mathbf{\Lambda}\|_{1,1}, \quad (5)$$

where  $\lambda_1$  and  $\lambda_2$  are positive parameters and  $\mathbf{\Lambda} = [\mathbf{\Lambda}^1, \mathbf{\Lambda}^2, \dots, \mathbf{\Lambda}^D]$  is the sparse coefficient matrix corresponding to occlusion. The  $\ell_1$ -norm of matrix  $\mathbf{\Lambda}$  is defined as  $\|\mathbf{\Lambda}\|_{1,1} = \sum_{i,j} |\Lambda_{i,j}|$ . Note that the idea of exploiting the sparsity of occlusion term has been studied by Wright *et al.* [16] and Candes *et al.* [30].

Once  $\mathbf{\Gamma}, \mathbf{\Lambda}$  are computed, the effect of occlusion can be removed by setting  $\tilde{\mathbf{Y}}^i = \mathbf{Y}^i - \mathbf{B}^i \mathbf{\Lambda}^i$ . One can then declare the class label associated to an observed vector as

$$\hat{j} = \arg \min_j \sum_{i=1}^D \|\mathbf{Y}^i - \mathbf{X}^i \delta_j^i(\mathbf{\Gamma}^i) - \mathbf{B}^i \mathbf{\Lambda}^i\|_F^2. \quad (6)$$

#### C. Optimization algorithm

Optimization problem (5) is convex but difficult to solve due to the joint sparsity constraint. In this section, we present an approach based on the classical alternating direction method of multipliers (ADMM) [31], [32]. Note that the optimization problem (1) can be solved by setting  $\lambda_2$  equal to zero. Let

$$\mathcal{C}(\mathbf{\Gamma}, \mathbf{\Lambda}) = \frac{1}{2} \sum_{i=1}^D \|\mathbf{Y}^i - \mathbf{X}^i \mathbf{\Gamma}^i - \mathbf{B}^i \mathbf{\Lambda}^i\|_F^2.$$



Then, our goal is to solve the following optimization problem

$$\min_{\Gamma, \Lambda} \mathcal{C}(\Gamma, \Lambda) + \lambda_1 \|\Gamma\|_{1,q} + \lambda_2 \|\Lambda\|_1. \quad (7)$$

In ADMM the idea is to decouple  $\mathcal{C}(\Gamma, \Lambda)$ ,  $\|\Gamma\|_{1,q}$  and  $\|\Lambda\|_1$  by introducing auxiliary variables to reformulate the problem into a constrained optimization problem

$$\min_{\Gamma, \Lambda, \mathbf{U}, \mathbf{V}} \mathcal{C}(\Gamma, \Lambda) + \lambda_1 \|\mathbf{V}\|_{1,q} + \lambda_2 \|\mathbf{U}\|_1 \quad \text{s. t.} \\ \Gamma = \mathbf{V}, \Lambda = \mathbf{U}. \quad (8)$$

Since, (8) is an equally constrained problem, the Augmented Lagrangian method (ALM) [31] can be used to solve the problem. This can be done by minimizing the augmented Lagrangian function  $f_{\alpha_\Gamma, \alpha_\Lambda}(\Gamma, \Lambda, \mathbf{V}, \mathbf{U}; \mathbf{A}_\Lambda, \mathbf{A}_\Gamma)$  defined as

$$\mathcal{C}(\Gamma, \Lambda) + \lambda_2 \|\mathbf{U}\|_1 + \langle \mathbf{A}_\Lambda, \Lambda - \mathbf{U} \rangle + \frac{\alpha_\Lambda}{2} \|\Lambda - \mathbf{U}\|_F^2 + \\ \lambda_1 \|\mathbf{V}\|_{1,q} + \langle \mathbf{A}_\Gamma, \Gamma - \mathbf{V} \rangle + \frac{\alpha_\Gamma}{2} \|\Gamma - \mathbf{V}\|_F^2, \quad (9)$$

where  $\mathbf{A}_\Lambda$  and  $\mathbf{A}_\Gamma$  are the multipliers of the two linear constraints, and  $\alpha_\Lambda, \alpha_\Gamma$  are the positive penalty parameters. The ALM algorithm solves  $f_{\alpha_\Gamma, \alpha_\Lambda}(\Gamma, \Lambda, \mathbf{V}, \mathbf{U}; \mathbf{A}_\Lambda, \mathbf{A}_\Gamma)$  with respect to  $\Gamma, \Lambda, \mathbf{U}$  and  $\mathbf{V}$  jointly, keeping  $\mathbf{A}_\Gamma$  and  $\mathbf{A}_\Lambda$  fixed and then updating  $\mathbf{A}_\Gamma$  and  $\mathbf{A}_\Lambda$  keeping the remaining variables fixed. Due to the separable structure of the objective function  $f_{\alpha_\Gamma, \alpha_\Lambda}$ , one can further simplify the problem by minimizing  $f_{\alpha_\Gamma, \alpha_\Lambda}$  with respect to variables  $\Gamma, \Lambda, \mathbf{U}$  and  $\mathbf{V}$ , separately. Different steps of the algorithm are given in Algorithm 1. In what follows, we describe each of the sub-optimization problems in detail.

**Algorithm 1:** Alternating Direction Method of Multipliers (ADMM).

**Initialize:**  $\Gamma_0, \mathbf{U}_0, \mathbf{V}_0, \mathbf{A}_{\Lambda,0}, \mathbf{A}_{\Gamma,0}, \alpha_\Gamma, \alpha_\Lambda$   
**While not converged do**  
 1.  $\Gamma_{t+1} = \arg \min_{\Gamma} f_{\alpha_\Gamma, \alpha_\Lambda}(\Gamma, \Lambda_t, \mathbf{U}_t, \mathbf{V}_t; \mathbf{A}_{\Gamma,t}, \mathbf{A}_{\Lambda,t})$   
 2.  $\Lambda_{t+1} = \arg \min_{\Lambda} f_{\alpha_\Gamma, \alpha_\Lambda}(\Gamma_{t+1}, \Lambda, \mathbf{U}_t, \mathbf{V}_t; \mathbf{A}_{\Gamma,t}, \mathbf{A}_{\Lambda,t})$   
 3.  $\mathbf{U}_{t+1} = \arg \min_{\mathbf{U}} f_{\alpha_\Gamma, \alpha_\Lambda}(\Gamma_{t+1}, \Lambda_{t+1}, \mathbf{U}, \mathbf{V}_t; \mathbf{A}_{\Gamma,t}, \mathbf{A}_{\Lambda,t})$   
 4.  $\mathbf{V}_{t+1} = \arg \min_{\mathbf{V}} f_{\alpha_\Gamma, \alpha_\Lambda}(\Gamma_{t+1}, \Lambda_{t+1}, \mathbf{U}_{t+1}, \mathbf{V}; \mathbf{A}_{\Gamma,t}, \mathbf{A}_{\Lambda,t})$   
 5.  $\mathbf{A}_{\Gamma,t+1} \doteq \mathbf{A}_{\Gamma,t} + \alpha_\Gamma(\Gamma_{t+1} - \mathbf{U}_{t+1})$   
 6.  $\mathbf{A}_{\Lambda,t+1} \doteq \mathbf{A}_{\Lambda,t} + \alpha_\Lambda(\Lambda_{t+1} - \mathbf{V}_{t+1})$

1) *Update step for  $\Gamma$ :* The first sub-optimization problem involves the minimization of  $f_{\alpha_\Gamma, \alpha_\Lambda}(\Gamma, \Lambda, \mathbf{V}, \mathbf{U}; \mathbf{A}_\Lambda, \mathbf{A}_\Gamma)$  with respect to  $\Gamma$ . It has the quadratic structure, which is easy to solve by setting the first-order derivative equal to zero. Furthermore, the loss function  $\mathcal{C}(\Gamma, \Lambda)$  is a sum of convex functions associated with sub-matrices  $\Gamma^i$ , one can seek for  $\Gamma_{t+1}^i$ ,  $i = 1, \dots, D$ , which has the following solution

$$\Gamma_{t+1}^i = (\mathbf{X}^{iT} \mathbf{X}^i + \alpha_\Gamma \mathbf{I})^{-1} (\mathbf{X}^{iT} (\mathbf{Y}^i - \Lambda_t^i) + \alpha_\Gamma \mathbf{V}_t^i + \mathbf{A}_{\Gamma,t}^i),$$

where  $\mathbf{I}$  is  $p \times p$  identity matrix and  $\Lambda_t^i, \mathbf{V}_t^i$  and  $\mathbf{A}_{\Gamma,t}^i$  are sub-matrices of  $\Lambda_t, \mathbf{V}_t$  and  $\mathbf{A}_{\Gamma,t}$ , respectively.

2) *Update step for  $\Lambda$ :* The second sub-optimization problem is similar in nature, whose solution is given below

$$\Lambda_{t+1}^i = (1 + \alpha_\Lambda)^{-1} (\mathbf{Y}^i - \mathbf{X}^i \Gamma_{t+1}^i + \alpha_\Lambda \mathbf{U}_t^i - \mathbf{A}_{\Lambda,t}^i),$$

where  $\mathbf{U}_t^i$  and  $\mathbf{A}_{\Lambda,t}^i$  are sub-matrices of  $\mathbf{U}_t$  and  $\mathbf{A}_{\Lambda,t}$ , respectively.

3) *Update step for  $\mathbf{U}$ :* The third sub-optimization problem is with respect to  $\mathbf{U}$ , which is the standard  $\ell_1$  minimization problem which can be recast as

$$\min_{\mathbf{U}} \frac{1}{2} \|\Lambda_{t+1} + \alpha_\Lambda^{-1} \mathbf{A}_{\Lambda,t} - \mathbf{U}\|_F^2 + \frac{\lambda_2}{\alpha_\Lambda} \|\mathbf{U}\|_1. \quad (10)$$

Equation (10) is the well-known shrinkage problem whose solution is given by

$$\mathbf{U}_{t+1} = \mathcal{S} \left( \Lambda_{t+1} + \alpha_\Lambda^{-1} \mathbf{A}_{\Lambda,t}, \frac{\lambda_2}{\alpha_\Lambda} \right),$$

where  $\mathcal{S}(a, b) = \text{sgn}(a)(|a| - b)$  for  $|a| \geq b$  and zero otherwise.

4) *Update step for  $\mathbf{V}$ :* The final suboptimization problem is with respect to  $\mathbf{V}$  which can be reformulated as

$$\min_{\mathbf{V}} \frac{1}{2} \|\Gamma_{t+1} + \alpha_\Gamma^{-1} \mathbf{A}_{\Gamma,t} - \mathbf{V}\|_F^2 + \frac{\lambda_1}{\alpha_\Gamma} \|\mathbf{V}\|_{1,q}. \quad (11)$$

Due to the separable structure of (11), it can be solved by minimizing with respect to each row of  $\mathbf{V}$  separately. Let  $\gamma_{i,t+1}, \mathbf{a}_{\Gamma,i,t}$  and  $\mathbf{v}_{i,t+1}$  be rows of matrices  $\Gamma_{t+1}, \mathbf{A}_{\Gamma,t}$  and  $\mathbf{V}_{t+1}$ , respectively. Then for each  $i = 1, \dots, p$  we solve the following sub-problem

$$\mathbf{v}_{i,t+1} = \arg \min_{\mathbf{v}} \frac{1}{2} \|\mathbf{z} - \mathbf{v}\|_2^2 + \eta \|\mathbf{v}\|_q, \quad (12)$$

where  $\mathbf{z} = \gamma_{i,t+1} - \mathbf{a}_{\Gamma,i,t} \alpha_\Gamma^{-1}$  and  $\eta = \frac{\lambda_1}{\lambda_2}$ . One can derive the solution for (12) for any  $q$ . In this paper, we only focus on the case when  $q = 2$ . The solution of (12) has the following form

$$\mathbf{v}_{i,t+1} = \left( 1 - \frac{\eta}{\|\mathbf{z}\|_2} \right)_+ \mathbf{z},$$

where  $(\mathbf{v})_+$  is a vector with entries receiving values  $\max(v_i, 0)$ .

Our proposed Sparse Multimodal Biometrics Recognition (SMBR) method is summarized in Algorithm 2. We refer to the robust method taking sparse error into account as SMBR-E (SMBR with error), and the initial case where it is not taken account as SMBR-WE (SMBR without error).

**Algorithm 2:** Sparse Multimodal Biometrics Recognition (SMBR).

**Input:** Training samples  $\{\mathbf{X}_i\}_{i=1}^D$ , test sample  $\{\mathbf{Y}_i\}_{i=1}^D$ , Occlusion basis  $\{\mathbf{B}_j\}_{j=1}^D$

**Procedure:** Obtain  $\hat{\Gamma}$  and  $\hat{\Lambda}$  by solving

$$\hat{\Gamma}, \hat{\Lambda} = \arg \min_{\Gamma, \Lambda} \frac{1}{2} \sum_{i=1}^D \|\mathbf{Y}^i - \mathbf{X}^i \Gamma^i - \mathbf{B}^i \Lambda^i\|_F^2 + \lambda_1 \|\Gamma\|_{1,q} + \lambda_2 \|\Lambda\|_1,$$

**Output:**

$$\text{identity}(\mathbf{Y}) = \arg \min_j \sum_{i=1}^D \|\mathbf{Y}^i - \mathbf{X}^i \delta_j^i(\hat{\Gamma}^i) - \mathbf{B}^i \hat{\Lambda}^i\|_F^2.$$

### III. QUALITY BASED FUSION

Ideally a fusion mechanism should give more weights to the more reliable modalities. Hence, the concept of quality is important in multimodal fusion. A quality measure based on sparse representation was introduced for faces in [16]. To decide whether a given test sample has good quality or not,

its Sparsity Concentration Index (SCI) was calculated. Given a coefficient vector  $\gamma \in \mathbb{R}^p$ , the SCI is given as:

$$SCI(\gamma) = \frac{C \cdot \max_{i \in \{1, \dots, C\}} \|\delta_i(\gamma)\|_1}{\|\gamma\|_1} - 1$$

where,  $\delta_i$  is the indicator function keeping the coefficients corresponding to the  $i^{th}$  class and setting others to zero. SCI values close to 1 correspond to the case where the test sample can be represented well using the samples of a single class, hence is of high quality. On the other hand, samples with SCI close to 0 are not similar to any of the classes, and hence are of poor quality. This can be easily extended to the multimodal case using the joint sparse representation matrix  $\hat{\Gamma}$ . In this case, we can define the quality,  $q_j^i$  for sample  $\mathbf{y}_j^i$  as:

$$q_j^i = SCI(\hat{\Gamma}_j^i)$$

where,  $\hat{\Gamma}_j^i$  is the  $j^{th}$  column of  $\hat{\Gamma}^i$ . Given this quality measure, the classification rule (2) can be modified to include the quality measure.

$$\hat{j} = \arg \min_j \sum_{i=1}^D \sum_{k=1}^{d_i} q_k^i \|\mathbf{y}_k^i - \mathbf{X}^i \delta_j(\Gamma_k^i)\|_F^2, \quad (13)$$

where,  $\delta_j$  is the indicator function retaining the coefficients corresponding to  $j^{th}$  class.

#### IV. KERNEL SPACE MULTIMODAL BIOMETRICS RECOGNITION

The class identities in the multibiometric dataset may not be linearly separable. Hence, we also extend the sparse multimodal fusion framework to kernel space. The kernel function,  $\kappa : \mathbb{R}^n \times \mathbb{R}^n$ , is defined as the inner product

$$\kappa(\mathbf{x}_i, \mathbf{x}_j) = \langle \phi(\mathbf{x}_i), \phi(\mathbf{x}_j) \rangle$$

where,  $\phi$  is an implicit mapping projecting the vector  $\mathbf{x}$  into a higher dimensional space.

##### A. Multivariate kernel sparse representation

Considering the general case of  $D$  modalities with  $\{\mathbf{Y}^i\}_{i=1}^D$  as a set of  $d_i$  observations, the feature space representation can be written as:

$$\Phi(\mathbf{Y}^i) = [\phi(\mathbf{y}_1^i), \phi(\mathbf{y}_2^i), \dots, \phi(\mathbf{y}_{d_i}^i)]$$

Similarly, the dictionary of training samples for modality  $i = 1, \dots, D$  can be represented in feature space as

$$\Phi(\mathbf{X}^i) = [\phi(\mathbf{x}_1^i), \phi(\mathbf{x}_2^i), \dots, \phi(\mathbf{x}_{d_i}^i)]$$

As in joint linear space representation, we have:

$$\Phi(\mathbf{Y}^i) = \Phi(\mathbf{X}^i) \Gamma^i$$

where,  $\Gamma^i$  is the coefficient matrix associated with modality  $i$ . Incorporating information from all the sensors, we seek to solve the following optimization problem similar to the linear case:

$$\hat{\Gamma} = \arg \min_{\Gamma} \frac{1}{2} \sum_{i=1}^D \|\Phi(\mathbf{Y}^i) - \Phi(\mathbf{X}^i) \Gamma^i\|_F^2 + \lambda \|\Gamma\|_{1,q} \quad (14)$$

where,  $\Gamma = [\Gamma^1, \Gamma^2, \dots, \Gamma^D]$ . It is clear that the information from all modalities are integrated via the shared sparsity pattern of the matrices  $\{\Gamma^i\}_{i=1}^D$ . This can be reformulated in terms of kernel matrices as:

$$\hat{\Gamma} = \arg \min_{\Gamma} \frac{1}{2} \sum_{i=1}^D (\text{trace}(\Gamma^{iT} \mathbf{K}_{\mathbf{X}^i, \mathbf{X}^i} \Gamma^i) - 2\text{trace}(\mathbf{K}_{\mathbf{X}^i, \mathbf{Y}^i} \Gamma^i)) + \lambda \|\Gamma\|_{1,q} \quad (15)$$

where, the kernel matrix  $\mathbf{K}_{\mathbf{A}, \mathbf{B}}$  is defined as:

$$\mathbf{K}_{\mathbf{A}, \mathbf{B}}(i, j) = \langle \phi(\mathbf{a}_i), \phi(\mathbf{b}_j) \rangle \quad (16)$$

$\mathbf{a}_i$  and  $\mathbf{b}_j$  being  $i^{th}$  and  $j^{th}$  columns of  $\mathbf{A}$  and  $\mathbf{B}$  respectively.

##### B. Optimization Algorithm

Similar to the linear fusion method, we apply the alternating direction method to efficiently solve the problem for kernel fusion. The method splits the variable  $\Gamma$  such that the new problem has two convex functions. This is done by introducing a new variable  $\mathbf{V}$  and reformulating the problems (15) and (??) as:

$$\arg \min_{\Gamma, \mathbf{V}} \frac{1}{2} \sum_{i=1}^{N_K} (\text{trace}(\Gamma^{iT} \mathbf{K}_{\mathbf{X}^i, \mathbf{X}^i} \Gamma^i) - 2\text{trace}(\mathbf{K}_{\mathbf{X}^i, \mathbf{Y}^i} \Gamma^i)) + \lambda \|\mathbf{V}\|_{1,q} \text{ s.t. } \Gamma = \mathbf{V} \quad (17)$$

where,  $N_K$  is the number of kernels in (15) and (??). Rewriting the problem using the Lagrangian multiplier, the optimization problem becomes:

$$\arg \min_{\Gamma, \mathbf{V}} \frac{1}{2} \sum_{i=1}^{N_K} (\text{trace}(\Gamma^{iT} \mathbf{K}_{\mathbf{X}^i, \mathbf{X}^i} \Gamma^i) - 2\text{trace}(\mathbf{K}_{\mathbf{X}^i, \mathbf{Y}^i} \Gamma^i)) + \lambda \|\mathbf{V}\|_{1,q} + \langle \mathbf{B}, \Gamma - \mathbf{V} \rangle + \frac{\beta_W}{2} \|\Gamma - \mathbf{V}\|_F^2 \quad (18)$$

which upon re-arranging reduces to:

$$\arg \min_{\Gamma, \mathbf{V}} \frac{1}{2} \sum_{i=1}^{N_K} (\text{trace}(\Gamma^{iT} \mathbf{K}_{\mathbf{X}^i, \mathbf{X}^i} \Gamma^i) - 2\text{trace}(\mathbf{K}_{\mathbf{X}^i, \mathbf{Y}^i} \Gamma^i)) + \lambda \|\mathbf{V}\|_{1,q} + \frac{\beta_W}{2} \|\Gamma - \mathbf{V} + \frac{1}{\beta_W} \mathbf{B}\|_F^2 \quad (19)$$

The optimization method is summarized in Algorithm 3. It should be pointed out that each step has a simple closed-form expression.

##### Algorithm 3: Alternating Direction Method of Multipliers (ADMM) in kernel space.

**Initialize:**  $\Gamma_0, \mathbf{V}_0, \mathbf{B}_0, \beta_W$   
**While not converged do**  
 1.  $\Gamma_{t+1} = \arg \min_{\Gamma} \frac{1}{2} \sum_{i=1}^{N_K} (\text{trace}(\Gamma^{iT} \mathbf{K}_{\mathbf{X}^i, \mathbf{X}^i} \Gamma^i) - 2\text{trace}(\mathbf{K}_{\mathbf{X}^i, \mathbf{Y}^i} \Gamma^i)) + \lambda \|\mathbf{V}_t\|_{1,q} + \frac{\beta_W}{2} \|\Gamma - \mathbf{V}_t + \frac{1}{\beta_W} \mathbf{B}_t\|_F^2$   
 2.  $\mathbf{V}_{t+1} = \arg \min_{\mathbf{V}} \lambda \|\mathbf{V}\|_{1,q} + \frac{\beta_W}{2} \|\Gamma_{t+1} - \mathbf{V}_t + \frac{1}{\beta_W} \mathbf{B}_t\|_F^2$   
 3.  $\mathbf{B}_{t+1} = \mathbf{B}_t + \beta_W(\Gamma_{t+1} - \mathbf{V}_{t+1})$

1) *Update steps for  $\Gamma_t$ :*  $\Gamma_{t+1}$  is obtained by updating each sub-matrix  $\Gamma_t^i$ ,  $i = 1, \dots, N_K$  as:

$$\Gamma_t^i = (\mathbf{K}_{\mathbf{X}^i, \mathbf{X}^i} + \beta_W \mathbf{I})^{-1} (\mathbf{K}_{\mathbf{X}^i, \mathbf{Y}^i} + \beta_W \mathbf{V}_t^i - \mathbf{B}_t^i) \quad (20)$$

where,  $\mathbf{I}$  is an identity matrix and  $\mathbf{V}_t^i$ ,  $\mathbf{B}_t^i$  are sub-matrices of  $\mathbf{V}_t$  and  $\mathbf{B}_t$  respectively.



2) *Update steps for  $\mathbf{V}_t$* : The update equation for  $\mathbf{V}_t$  is same as in the linear fusion case using (11) and (12), replacing  $\mathbf{A}_{\Gamma,t}$  and  $\alpha_{\Gamma}$  with  $\mathbf{B}_t$  and  $\beta_W$  respectively.

### C. Classification

Once  $\mathbf{\Gamma}$  is obtained, classification can be done by assigning the class label as:

$$\hat{j} = \arg \min_j \sum_{i=1}^{N_K} \|\Phi(\mathbf{Y}^i) - \Phi(\mathbf{X}_j^i) \hat{\mathbf{\Gamma}}_j^i\|_F^2$$

or in terms of kernel matrices as:

$$\begin{aligned} \hat{j} = \arg \min_j \sum_{i=1}^{N_K} & (\text{trace}(\mathbf{K}_{\mathbf{Y}\mathbf{Y}}) - 2\text{trace}(\hat{\mathbf{\Gamma}}_j^{iT} \mathbf{K}_{\mathbf{X}_j^i \mathbf{Y}} \hat{\mathbf{\Gamma}}_j^i) \\ & + \text{trace}(\hat{\mathbf{\Gamma}}_j^{iT} \mathbf{K}_{\mathbf{X}_j^i \mathbf{X}_j^i} \hat{\mathbf{\Gamma}}_j^i)) \end{aligned} \quad (21)$$

Here,  $\mathbf{X}_j^i$  is the sub-dictionary associated with  $j^{th}$  class and  $\hat{\mathbf{\Gamma}}_j^i$  is the coefficient matrix associated with this class.

The classification rule can be further extended to include the quality measure as in (13). But, we skip this step here, as we wish to study the effect of kernel representation and quality separately.

Multivariate Kernel Sparse Recognition (kerSMBR) algorithm is summarized in Algorithm 4:

**Algorithm 4:** Kernel Sparse Multimodal Biometrics Recognition (kerSMBR).

**Input:** Training samples  $\{\mathbf{X}_i\}_{i=1}^D$ , test sample  $\{\mathbf{Y}_i\}_{i=1}^D$

**Procedure:** Obtain  $\hat{\mathbf{\Gamma}}$  by solving

$$\hat{\mathbf{\Gamma}} = \arg \min_{\mathbf{\Gamma}} \frac{1}{2} \sum_{i=1}^D \|\Phi(\mathbf{Y}^i) - \Phi(\mathbf{X}^i) \mathbf{\Gamma}^i\|_F^2 + \lambda \|\mathbf{\Gamma}\|_{1,q} \quad (22)$$

**Output:**  $\text{identity}(\mathbf{Y}) = \arg \min_j \sum_{i=1}^D (\text{trace}(\mathbf{K}_{\mathbf{Y}\mathbf{Y}}) - 2\text{trace}(\hat{\mathbf{\Gamma}}_j^{iT} \mathbf{K}_{\mathbf{X}_j^i \mathbf{Y}} \hat{\mathbf{\Gamma}}_j^i) + \text{trace}(\hat{\mathbf{\Gamma}}_j^{iT} \mathbf{K}_{\mathbf{X}_j^i \mathbf{X}_j^i} \hat{\mathbf{\Gamma}}_j^i))$

## V. EXPERIMENTS

We evaluated our algorithm on two publicly available datasets - the WVU Multimodal dataset [33] and the AR face dataset [34]. In the first experiment, we tested on the WVU dataset, which is one of the few publicly available datasets which allows fusion at image level. It is a challenging dataset consisting of samples from different biometric modalities for each subject.

In the second experiment, we show the applicability of our method to fusing information from *weak* biometrics extracted from face images. In particular, the periocular region has been shown to be a useful biometric [35]. Similarly, the nose region has also been explored as a biometric [36]. Sinha *et al* [37] have demonstrated that eyebrows are important for face recognition. However, each of these sub-regions may not be as discriminative as the whole face. The challenge for fusion algorithms is to be able to combine these weak modalities with a strong modality based on the whole face [38]. We demonstrate how our framework can be extended to address this problem. Further, we also show the effects of noise and

occlusion on the performance of different algorithms. In all the experiments  $\mathbf{B}_i$  was set to be identity for convenience, *i.e.*, we assume background noise to be sparse in image domain.

### A. WVU Multimodal Dataset

The WVU multimodal dataset is a comprehensive collection of different biometric modalities such as fingerprint, iris, palmprint, hand geometry and voice from subjects of different age, gender and ethnicity as described in Table I. It is a challenging dataset as many of these samples are corrupted with blur, occlusion and sensor noise as shown in Figure 2. Out of these, we chose iris and fingerprint modalities for testing the proposed algorithms. In total, there are 2 iris (right and left iris) and 4 fingerprint modalities. Also, the evaluation was done on a subset of 219 subjects having samples in both modalities.



Fig. 2: Examples of challenging images from the WVU Multimodal dataset. The images shown above suffer from various artifacts such as sensor noise, blur and occlusion.

Biometric Modality	# of subjects	# of samples
Iris	244	3099
Fingerprint	272	7219
Palm	263	683
Hand	217	3062
Voice	274	714

TABLE I: WVU Biometric Data

1) *Preprocessing*: Robust pre-processing of images was done before feature extraction. Iris images were segmented using the method proposed in [39]. Following the segmentation step,  $25 \times 240$  iris templates were generated by re-sampling using the publicly available code of Masek *et al.* [40]. Fingerprint images were enhanced using the filtering methods described in [41], and then the core point was detected from the enhanced images [42]. Features were then extracted around the detected core point.

2) *Feature Extraction*: Gabor features were extracted from the processed images as they have been shown to give good performance on both fingerprints [42] and iris [43]. For fingerprint samples, the processed images were convolved with Gabor filters at 8 different orientations. Circular tessellations were extracted around the core point for all the filtered images similar to [42]. The tessellation consisted of 15 concentric bands, each of width 5 pixels and divided into 30 sectors. The mean values for each sector were concatenated to form the feature vector of size  $3600 \times 1$ . Features for iris images were formed by convolving the templates with a log-Gabor filter at a single scale, and vectorizing the template to give a  $6000 \times 1$  dimensional feature.




Fig. 3: CMCs (Cumulative Match Curve) for individual modalities using (a) SMBR-E, (b) SMBR-WE, (c) SLR and (d) SVM methods.




Fig. 4: CMCs for multimodal fusion using (a) four fingerprints, (b) two irises and (c) all modalities.

	Finger 1	Finger 2	Finger 3	Finger 4	Iris 1	Iris 2
SMBR-WE	<b>68.1 ± 1.1</b>	<b>88.4 ± 1.2</b>	<b>69.2 ± 1.5</b>	<b>87.5 ± 1.5</b>	60.0 ± 1.5	62.1 ± 0.4
SMBR-E	67.1 ± 1.0	87.9 ± 0.8	67.4 ± 1.9	86.9 ± 1.5	<b>62.5 ± 1.2</b>	<b>64.3 ± 1.0</b>
SLR	67.4 ± 1.9	87.9 ± 1.3	66.0 ± 2.2	87.5 ± 1.3	57.1 ± 3.0	57.9 ± 2.7
SVM	41.1 ± 5.0	75.5 ± 2.2	49.2 ± 1.6	67.0 ± 8.3	44.3 ± 1.2	45.0 ± 2.9

TABLE II: Rank one recognition performance for individual modalities.

	SMBR-WE	SMBR-E	SLR-Sum	SLR-Major	SVM-Sum	SVM-Major	MKLFusion
4 Fingerprints	<b>97.9 ± 0.4</b>	97.6 ± 0.6	96.3 ± 0.8	74.2 ± 0.7	90.0 ± 2.2	73.0 ± 1.5	86.2 ± 1.2
2 Irises	76.5 ± 1.6	<b>78.2 ± 1.2</b>	72.7 ± 4.0	64.2 ± 2.7	62.8 ± 2.6	49.3 ± 2.0	76.8 ± 2.5
All modalities	<b>98.7 ± 0.2</b>	98.6 ± 0.5	97.6 ± 0.4	84.4 ± 0.9	94.9 ± 1.5	81.3 ± 1.7	89.8 ± 0.9

TABLE III: Rank one recognition performance for the WVU Multimodal dataset.

	SMBR-WE	SMBR-E	SLR-Sum	SLR-Major	SVM-Sum	SVM-Major
4 Fingerprints	<b>98.2 ± 0.5</b>	98.1 ± 0.5	97.5 ± 0.5	86.3 ± 0.6	93.6 ± 1.6	85.5 ± 0.9
2 Irises	76.9 ± 1.2	<b>78.8 ± 1.7</b>	74.1 ± 1.0	67.2 ± 2.4	64.3 ± 3.3	51.6 ± 2.0
All modalities	<b>98.8 ± 0.4</b>	98.6 ± 0.3	98.2 ± 0.2	93.8 ± 0.9	95.5 ± 1.5	93.3 ± 1.2

TABLE IV: Rank one recognition performance using the proposed quality measure.

3) *Experimental Set-up*: The dataset was randomly divided into 4 training samples per class (1 sample here is 1 data sample each from 6 modalities) and the remaining 519 samples were used for testing. The recognition result was averaged over 5 runs. The proposed methods were compared with state-of-the-art classification methods such as sparse logistic regression (SLR) [44] and SVM [45]. As these methods cannot handle multiple modalities, we explored score-level and decision-level fusion methods for combining the results of individual modalities. For score-level fusion, the probability outputs for test sample of each modality,  $\{y_i\}_{i=1}^6$  were added together to give the final score vector. Classification was based upon the final score values. For decision-level fusion, the subject chosen by the maximum number of modalities was taken to be from the correct class. We further compared with the efficient multiclass implementation of MKL algorithm [46]. The proposed linear and kernel fusion techniques were tested separately and compared them with the linear and kernel versions of SLR, SVM and MKL algorithms. We denote the score-level fusion of these methods as SLR-Sum and SVM-Sum, and the decision-level fusion as SLR-Major and SVM-Major. MKL based method is denoted as MKLFusion. We report mean and standard deviation of rank one recognition rates for all the methods. We also show Cumulative Match Curves (CMCs) for all the classifiers. CMC is a performance measure for biometric recognition systems and has been shown to be equivalent to ROC of the system [47].

a) *Linear Fusion*: The recognition performances of SMBR-WE and SMBR-E was compared with linear SVM and linear SLR classification methods. The parameters  $\lambda_1$  and  $\lambda_2$  were set to 0.01.

- *Comparison of Methods*: Figure 3 and Table II show the performance on individual modalities. All the classifiers show a similar trend. The performance for all of them are lower on iris images and fingers 1 and 3. The proposed method show superior performance on all the modalities. Figure 4 and Table III show the recognition performance for different fusion settings. The proposed SMBR approach outperforms existing classification techniques.

Both SMBR-E and SMBR-WE have similar performance, though the latter seems to give a slightly better performance. This may be due to the penalty on the sparse error, though the error may not be sparse in the image domain. Further, sum-based fusion shows a superior performance over voting-based methods. MKL based method shows good performance for iris fusion, but the performance drops for other two settings. This may be because by weighing kernels during training, it loses flexibility while testing when number of modalities increase.

- *Fusion with quality*: Clearly, different modalities have different levels of performance. Hence, we studied the effect of the proposed quality measure on the performance of different methods. For a consistent comparison, the quality values produced by SMBR-E method was used for all the algorithms. Table IV shows the performance for the three fusion settings. The effect of including the quality measure can be studied by comparing with Table III. Clearly, the recognition rate increases for all the methods across the fusion settings. Again SMBR-E and SMBR-WE give the best performances among all the methods.
- *Effect of joint sparsity*: We also studied the effect of joint sparsity constraint on the recognition performance. For this, SMBR-WE algorithm was run for different values of  $\lambda_1$ . Figure 5 shows the rank one recognition variation across  $\lambda_1$  values for different fusion settings. All the curves show a sharp increase in performance around  $\lambda_1 = 0$ . Further, the increase is more for iris fusion, which shows around 5% improvement at  $\lambda_1 = 0.005$  over  $\lambda_1 = 0$ . This shows that imposing joint sparsity constraint is important for fusion. Moreover, it helps in regulating fusion performance, when the reconstruction error alone is not sufficient to distinguish between different classes. The performance is then stable across  $\lambda_1$  values, and starts decreasing slowly after reaching the optimum performance.
- *Variation with number of training samples*: We varied the number of training samples and studied the effect




Fig. 5: Variation of recognition performance with different values of sparsity constraint,  $\lambda_1$ .

on the top four algorithms. Figure 6 shows the variation for fusion of all the modalities. It can be seen that SMBR-WE and SMBR-E are stable across number of training samples, whereas the performance of SLR and MKLFusion based methods fall sharply. The fall in performance of SLR and MKLFusion can be attributed to the discriminative approaches of these methods, as well as score-based fusion, as the fusion further reduces the recognition performance when individual classifiers are not good.




Fig. 6: Variation of recognition performance with number of training samples.

- *Comparison with other score-based fusion methods:* Although sum-based fusion is a popular technique for score fusion, some other techniques have also been proposed. We evaluated the performance of likelihood-based fusion method proposed in [48]. The results are shown in Table V. The method does not show good performance as it models score distribution as Gaussian Mixture Model. However, it is difficult to model score distribution due to large variations in data samples. The method is also affected by the curse of dimensionality.

	2 irises	4 fingerprints	All modalities
SLR-Likelihood	66.6	83.5	75.1
SVM-Likelihood	50.7	31.9	31.0

TABLE V: Fusion performance with likelihood-based method [48].

b) **Kernel Fusion:** We further compared the performances of proposed kerSMBR with kernel SVM, kernel SLR and MKLFusion methods. In the experiments, we used Radial Basis Function (RBF) as the kernel, given as:

$$\kappa(\mathbf{x}_i, \mathbf{x}_j) = \exp\left(-\frac{\|\mathbf{x}_i - \mathbf{x}_j\|_2^2}{\sigma^2}\right),$$

$\sigma$  being a parameter to control the width of the RBF. For MKLFusion, we gave linear, polynomial and RBF kernels as the base kernels for learning.

- *Hyperparameter tuning:* To fix the value of hyperparameter,  $\sigma$ , we iterated over different values of  $\sigma$ ,  $\{2^{-3}, 2^{-2}, \dots, 2^3\}$  for one set of training and test split of the data. The value of  $\sigma$  giving the maximum performance was fixed for each modality, and the performance was averaged over a few iterations. The weights  $\{\alpha_{ij}\}$  were set to 1 for composite kernel.  $\lambda$  and  $\beta_W$  were set to 0.01 and 0.01 respectively.
- *Comparison of methods:* Figure 7 shows the performance of different methods on individual modalities, and Figure 8 and Table VII on different fusion settings. Comparison of performance with linear fusion shows that the proposed kerSMBR significantly improves the performance on individual iris modalities as well as iris fusion. The performance on fingerprint modalities are similar, however the fusion of all 6 modalities (2 iris + 4 fingerprints) shows an improvement of 0.4%. kerSMBR also achieves the best accuracy among all the methods for different fusion settings. kerSLR scores better than kerSVM in all the cases, and its accuracy is close to kerSMBR. The performance of kerSLR is better than the linear counterpart, however kerSVM does not show much improvement.




Fig. 9: Face mask used to crop out different modalities.

## B. AR Face Dataset

The AR face dataset consists of faces with varying illumination, expression and occlusion conditions, captured in two sessions. We evaluated our algorithms on a set of 100 users. Images from the first session, 7 for each subject were used as training and the images from the second session, again 7 per subject, were used for testing. For testing the fusion algorithms, four weak modalities were extracted from the face images: left and right periocular, mouth and nose regions. This was done by applying rectangular masks as shown in Figure 9, and cropping out the respective regions. These, along with the whole face, were taken for fusion. Simple intensity values were




Fig. 7: CMCs for individual modalities using (a) kernel SVM, (b) kernel SLR and (c) kerSMBR.




Fig. 8: CMCs for different fusion methods for (a) four fingerprints, (b) two irises and (c) all modalities. Results for composite kernels using different techniques is shown in figure (d).

	Finger 1	Finger 2	Finger 3	Finger 4	Iris 1	Iris 2
kerSMBR	$66.3 \pm 1.7$	$87.1 \pm 1.0$	$69.1 \pm 2.1$	$86.4 \pm 1.5$	$70.3 \pm 1.8$	$71.0 \pm 1.6$
kerSLR	$65.8 \pm 1.8$	$86.9 \pm 1.7$	$68.3 \pm 2.0$	<b><math>89.5 \pm 1.6</math></b>	$65.1 \pm 1.7$	$66.8 \pm 1.1$
kerSVM	$48.4 \pm 5.4$	$76.7 \pm 2.3$	$50.2 \pm 1.9$	$68.4 \pm 7.4$	$43.9 \pm 1.1$	$44.6 \pm 3.0$

TABLE VI: Rank one recognition performance for individual modalities using kernel methods.



	kerSMBR	kerSLR-Sum	kerSLR-Major	kerSVM-Sum	kerSVM-Major	MKLFusion
4 Fingerprints	<b>97.9 ± 0.3</b>	96.8 ± 0.7	75.2 ± 0.7	93.2 ± 1.2	71.4 ± 1.3	88.7 ± 0.9
2 Irises	<b>84.7 ± 1.7</b>	83.7 ± 1.8	75.2 ± 1.2	62.2 ± 2.8	47.8 ± 2.4	76.9 ± 2.4
All modalities	<b>99.1 ± 0.2</b>	98.9 ± 0.1	87.9 ± 0.6	96.3 ± 0.8	79.5 ± 1.6	91.2 ± 1.0

TABLE VII: Rank one recognition performance for different fusion settings using kernel methods.

used as features for all of them. The experimental set-up was similar to the previous section. The parameter values,  $\lambda_1$  and  $\lambda_2$  were set to 0.003 and 0.002 respectively. Furthermore, we also studied the effect of noise and occlusion on recognition performance.

- *Comparison of methods:* Table VIII shows the performance of different algorithms on the face dataset. Here, SR (sparse representation) shows the classification result using just the whole face. Block Sparse Method is a recent block sparsity based face recognition algorithm [50] and FDDL [49] is a state-of-the-art discriminative dictionaries based technique, but using only single modality. Clearly, the SMBR approach achieves about 4 % improvement over other techniques. Thus, robust classification using multiple modalities results in a significant improvement over the current benchmark. Further, a comparison with discriminative methods such as SLR and SVM shows that they perform poorly compared to the proposed method. This is because weak modalities are hard to discriminate, hence score-level fusion with strong modality does not improve performance. On the other hand, by appropriately weighing different modalities, MKLFusion achieves better result. However, by imposing reconstruction and joint sparsity simultaneously, the proposed method is able to achieve superior performance.
- *Effect of noise:* In this experiment, test images were corrupted with white Gaussian noise of increasing variance,  $\sigma^2$ . Comparisons are shown in Figure 10. It can be seen that both SMBR, SR and Block Sparse methods are stable with noise. The performance of other algorithms degrade sharply with noise level. This also highlights the problem with MKLFusion, as it is not robust to degradation during testing.
- *Effect of occlusion:* In this experiment, a randomly chosen block of the test image was occluded. The recognition performance was studied with increasing block size. Figure 11 shows the performance of various algorithms with block size. SMBR-E is the most stable among all the methods due to robust handling of error. Recognition rates for other methods fall sharply with increasing block size.
- *Recognition in spite of disguise:* We also performed experiment on the rest of the AR face dataset, occluded by sun-glass and scarves. Similar to the above experiment, 7 frontal non-occluded images per subject, from the first session, were used for training, and 12 occluded images per person, from both the sessions were used for testing. Again the proposed SMBR-WE and SMBR-E methods outperformed the other methods. SMBR-E method gave the best performance, improving by 17.7% over the Block Sparse method.

Method	Scarves	Sun-glass	Overall
SMBR-WE	<b>86.2</b>	36.0	61.1
SMBR-E	80.0	<b>75.0</b>	<b>77.5</b>
SR	45.3	52.3	48.8
Block Sparse [50]	65.8	53.8	59.8
SLR-Sum	72.2	39.6	55.9
SVM-Sum	13.8	42.5	28.1
MKLFusion	47.7	13.0	30.3

TABLE IX: Rank one performance comparison of the proposed method.

- *Quality based fusion:* Quality determination is an important parameter in fusion here, as a strong modality is being combined with weak modalities. We studied the effect of quality measure introduced in Section III. However, in this case we fix the quality for strong modality, viz. whole face to be 1, while for the weak modalities, the SCI values were taken. The recognition performance for SMBR-E and SMBR-WE across different noise and occlusion levels was studied. Figure 12 show the performance comparison with the unweighted methods. Using quality, the recognition performance for SMBR-WE goes up to 97.4 % from 96.9 %, whereas for SMBR-E it increases to 97 % from 96 %. Similarly, results improve across different noise levels for both methods. However, SMBR-WE with quality shows worse performance as block size is increased. This may be because it does not handle sparse error, hence the quality values are not robust.

## VI. COMPUTATIONAL COMPLEXITY

The proposed algorithms are computationally efficient. The main steps of the algorithms are the update steps for  $\Gamma$ ,  $\Lambda$ ,  $\mathbf{U}$  and  $\mathbf{V}$ . For linear fusion, the update step for  $\Gamma$  involves computing  $(\mathbf{X}^T \mathbf{X}^i + \alpha_T \mathbf{I})^{-1}$  and four matrix multiplications. The first term is constant across iterations and can be pre-computed. Matrix multiplication for two matrices of sizes  $m \times n$  and  $n \times p$  can be done in  $\mathcal{O}(mnp)$  time. Hence, for a given training and test data, the computations are linear in feature dimension. Hence, large feature dimensions can be efficiently handled. Similarly, update step for  $\Lambda$  involves matrix multiplication  $\mathbf{X}^i \mathbf{\Gamma}^i$ . Update steps for  $\mathbf{U}$  and  $\mathbf{V}$  involves only scalar matrix computations and are very fast. Similarly in the kernel fusion, update for  $\Gamma$  involves calculating  $(\mathbf{K}_{\mathbf{X}^i, \mathbf{X}^i} + \beta_W \mathbf{I})^{-1}$ , which can be pre-computed. Other steps are similar to linear fusion. Classification step involves calculating the residual error for each class, and is efficient.

## VII. CONCLUSION

We have proposed a novel joint sparsity-based feature level fusion algorithm for multimodal biometrics recognition. The






Fig. 10: Effect of noise on recognition performance.




Fig. 11: Effect of occlusion on recognition performance.

Method	Recognition Rate (%)	Method	Recognition Rate (%)
SMBR-WE	<b>96.9</b>	SVM-Sum	86.7
SMBR-E	96	SLR-Sum	77.9
SR	91	FDDL [49]	91.9
Block Sparse [50]	92.2	MKLFusion	89.7

TABLE VIII: Rank one performance comparison of the proposed method.

algorithm is robust as it explicitly includes both noise and occlusion terms. An efficient algorithm based on alternative direction was proposed for solving the optimization problem. We also proposed a multimodal quality measure based on sparse representation. Further, the algorithm was extended to handle non-linear variations through kernel. Various experiments have shown that our method is robust and significantly improves the overall recognition accuracy.

#### ACKNOWLEDGMENT

The work of SS, VMP, and RC was partially supported by a MURI grant from the Army Research Office under the Grant W911NF-09-1-0383.

#### REFERENCES

- [1] A. Ross, K. Nandakumar, and A. K. Jain, *Handbook of Multibiometrics*. Springer, 2006.
- [2] A. Ross and A. K. Jain, "Multimodal biometrics: an overview," *Proc. European Signal Processing Conference*, pp. 1221–1224, Vienna, Austria, Sept. 2004.
- [3] P. Krishnasamy, S. Belongie, and D. Kriegman, "Wet fingerprint recognition: Challenges and opportunities," *International Joint Conference on Biometrics*, pp. 1–7, Washington DC, USA, Oct. 2011.
- [4] A. Klausner, A. Tengg, and B. Rinner, "Vehicle classification on multi-sensor smart cameras using feature- and decision-fusion," *IEEE Conference on Distributed Smart Cameras*, pp. 67–74, Vienna, Austria, Sept. 2007.
- [5] A. Rattani, D. Kisku, M. Bicego, and M. Tistarelli, "Feature level fusion of face and fingerprint biometrics," *IEEE International Conference on Biometrics: Theory, Applications, and Systems*, pp. 1–6, Washington DC, USA, Sept. 2007.
- [6] X. Zhou and B. Bhanu, "Feature fusion of face and gait for human recognition at a distance in video," *International Conference on Pattern Recognition*, vol. 4, pp. 529–532, Hong Kong, Aug. 2006.
- [7] A. A. Ross and R. Govindarajan, "Feature level fusion of hand and face biometrics," *Proc. of the SPIE*, vol. 5779, pp. 196–204, Orlando, USA, Mar. 2005.
- [8] M. Gönen and E. Alpaydın, "Multiple kernel learning algorithms," *Journal of Machine Learning Research*, vol. 12, pp. 2211–2268, 2011.
- [9] S. Kakade and D. Foster, "Multi-view regression via canonical correlation analysis," *Learning Theory*, pp. 82–96, 2007.
- [10] V. Sindhwani and D. Rosenberg, "An rkhs for multi-view learning and manifold co-regularization," *25th International Conference on Machine Learning*, pp. 976–983, Helsinki, July 2008.
- [11] J. Farquhar, H. Meng, S. Szedmak, D. Hardoon, and J. Shawe-taylor, "Two view learning: Svm-2k, theory and practice," *Advances in Neural Information Processing Systems*, Vancouver, Dec. 2006.
- [12] T. Diethe, D. Hardoon, and J. Shawe-Taylor, "Constructing nonlinear discriminants from multiple data views," *Machine Learning and Knowledge Discovery in Databases*, pp. 328–343, 2010.




Fig. 12: Effect of quality on recognition performance across (a) noise (b) random blocks.

- [13] S. Kim, A. Magnani, and S. Boyd, "Optimal kernel selection in kernel fisher discriminant analysis," *23rd International Conference on Machine Learning*, pp. 465–472, Pittsburgh, USA, June 2006.
- [14] V. M. Patel and R. Chellappa, "Sparse representations, compressive sensing and dictionaries for pattern recognition," *Asian Conference on Pattern Recognition*, pp. 325–329, Beijing, China, Nov. 2011.
- [15] V. M. Patel, R. Chellappa, and M. Tistarelli, "Sparse representations and random projections for robust and cancelable biometrics," *International Conference on Control, Automation, Robotics and Vision*, pp. 1–6, Guangzhou, China, Dec. 2010.
- [16] J. Wright, A. Y. Yang, A. Ganesh, S. S. Sastry, and Y. Ma, "Robust face recognition via sparse representation," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 31, pp. 210–227, Feb. 2009.
- [17] J. K. Pillai, V. M. Patel, R. Chellappa, and N. K. Ratha, "Secure and robust iris recognition using random projections and sparse representations," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 33, pp. 1877–1893, Sept. 2011.
- [18] P. Nagesh and B. Li, "A compressive sensing approach for expression-invariant face recognition," *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1518–1525, Miami, USA, June 2009.
- [19] V. M. Patel, T. Wu, S. Biswas, P. Phillips, and R. Chellappa, "Dictionary-based face recognition under variable lighting and pose," *IEEE Transactions on Information Forensics and Security*, vol. 7, pp. 954–965, June 2012.
- [20] Q. Zhang and B. Li, "Discriminative K-SVD for dictionary learning in face recognition," *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2691–2698, San Francisco, USA, June 2010.
- [21] J. Wright, Y. Ma, J. Mairal, G. Sapiro, T. Huang, and S. Yan, "Sparse representation for computer vision and pattern recognition," *Proceedings of the IEEE*, vol. 98, pp. 1031–1044, June 2010.
- [22] A. Wagner, J. Wright, A. Ganesh, Z. Zhou, H. Mobahi, and Y. Ma, "Towards a practical face recognition system: Robust alignment and illumination via sparse representation," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 34, pp. 372–386, Feb. 2012.
- [23] M. Yuan and Y. Lin, "Model selection and estimation in regression with grouped variables," *Journal of the Royal Statistical Society: Series B*, vol. 68, pp. 49–67, Feb. 2006.
- [24] L. Meier, S. V. D. Geer, and P. Bhlmann, "The group lasso for logistic regression," *Journal of the Royal Statistical Society: Series B*, vol. 70, pp. 53–71, Feb. 2008.
- [25] X.-T. Yuan and S. Yan, "Visual classification with multi-task joint sparse representation," *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 3493–3500, San Francisco, USA, June 2010.
- [26] H. Zhang, N. M. Nasrabadi, Y. Zhang, and T. S. Huang, "Multi-observation visual recognition via joint dynamic sparse representation," *International Conference on Computer Vision*, pp. 595–602, Barcelona, Spain, Nov. 2011.
- [27] S. Shekhar, V. M. Patel, N. M. Nasrabadi, and R. Chellappa, "Joint sparsity-based robust multimodal biometrics recognition," *ECCV Workshop on Information Fusion in Computer Vision for Concept Recognition (IFCVCR)*, Florence, Italy, Oct. 2012.
- [28] N. H. Nguyen, N. M. Nasrabadi, and T. D. Tran, "Robust multi-sensor classification via joint sparse representation," *International Conference on Information Fusion*, pp. 1–8, Chicago, USA, July 2011.
- [29] R. Tibshirani, "Regression shrinkage and selection via the lasso," *Journal of the Royal Statistical Society: Series B*, vol. 58, pp. 267–288, 1996.
- [30] E. J. Candes, X. Li, Y. Ma, and J. Wright, "Robust principal component analysis?" *Journal of ACM*, vol. 58, pp. 1–37, May 2011.
- [31] J. Yang and Y. Zhang, "Alternating direction algorithms for 11 problems in compressive sensing," *SIAM Journal on Scientific Computing*, vol. 33, pp. 250–278, 2011.
- [32] M. Afonso, J. Bioucas-Dias, and M. Figueiredo, "An augmented lagrangian approach to the constrained optimization formulation of imaging inverse problems," *IEEE Transactions on Image Processing*, vol. 20, pp. 681–695, March 2011.
- [33] S. S. S. Crialmeanu, A. Ross and L. Hornak, "A protocol for multi-biometric data acquisition, storage and dissemination," *In Technical Report, WVU, Lane Department of Computer Science and Electrical Engineering*, 2007.
- [34] A. Martinez and R. Benavente, "The AR face database," *CVC Technical Report*, June 1998.
- [35] U. Park, R. Jillela, A. Ross, and A. Jain, "Periocular biometrics in the visible spectrum," *IEEE Transactions on Information Forensics and Security*, vol. 6, pp. 96–106, March 2011.
- [36] A. Moorhouse, A. Evans, G. Atkinson, J. Sun, and M. Smith, "The nose on your face may not be so plain: Using the nose as a biometric," *International Conference on Crime Detection and Prevention*, pp. 1–6, London, UK, Dec. 2009.
- [37] P. Sinha, B. Balas, Y. Ostrovsky, and R. Russell, "Face recognition by humans: Nineteen results all computer vision researchers should know about," *Proceedings of the IEEE*, vol. 94, pp. 1948–1962, Nov. 2006.
- [38] H. Li, K.-A. Toh, and L. Li, *Advanced Topics In Biometrics*. World Scientific Publishing Co. Pte. Ltd., 2012.
- [39] S. Pundlik, D. Woodard, and S. Birchfield, "Non-ideal iris segmentation using graph cuts," *IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pp. 1–6, Anchorage, USA, June 2008.
- [40] L. Masek and P. Kovesi, "MATLAB source code for biometric identification system based on iris patterns," The University of Western Australia, Tech. Rep., 2003.
- [41] C. W. S. Chikkerur and V. Govindaraju, "A systematic approach for feature extraction in fingerprint images," *International Conference on Bioinformatics and its Applications*, pp. 344–350, Fort Lauderdale, USA, Dec. 2004.
- [42] A. Jain, S. Prabhakar, L. Hong, and S. Pankanti, "Filterbank-based fingerprint matching," *IEEE Transactions on Image Processing*, vol. 9, pp. 846–859, May 2000.
- [43] J. Daugman, "How iris recognition works," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 14, pp. 21–30, Jan. 2004.
- [44] B. Krishnapuram, L. Carin, M. Figueiredo, and A. Hartemink, "Sparse multinomial logistic regression: fast algorithms and generalization bounds," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 27, pp. 957–968, June 2005.
- [45] C. J. Burges, "A tutorial on support vector machines for pattern recognition," *Data Mining and Knowledge Discovery*, vol. 2, pp. 121–167, June 1998.
- [46] A. Rakotomamonjy, F. Bach, S. Canu, and Y. Grandvalet, "Simplemkl," *Journal of Machine Learning Research*, vol. 9, pp. 2491–2521, 2008.
- [47] R. Bolle, J. Connell, S. Pankanti, N. Ratha, and A. Senior, "The relation between the roc curve and the cmc," *Fourth IEEE Workshop on Automatic Identification Advanced Technologies*, pp. 15–20, 2005.
- [48] K. Nandakumar, Y. Chen, S. Dass, and A. Jain, "Likelihood ratio-based biometric score fusion," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 30, pp. 342–347, Feb. 2008.

- [49] X. F. M. Yang, L. Zhang and D. Zhang, "Fisher Discrimination Dictionary learning for sparse representation," *International Conference on Computer Vision*, pp. 543–550, Barcelona, Spain, Nov. 2011.
- [50] E. Elhamifar and R. Vidal, "Robust classification using structured sparse representation," *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1873–1879, Colorado Springs, June 2011.